

TECHNICAL SHEET OF CONFORMITY	SP0 ADJUSTABLE PEDESTALS	PAGE NO. REV NO. REV DATE.	1/1 10 21.03.2022
-------------------------------	------------------------------------	----------------------------------	-------------------------

DEFINITION

- SURPLOT® pedestals are made of PP (polypropylene copolymer)
- 200 mm outer diameter of 1 base unit with a circular cutaway.
- 120 mm outer diameter of 1 head.
- The available height of SURPLOT® SP0 screwjack pedestal is between 26 to 35 mm with a circular cutaway.

SPECIFICATIONS

TEST METHOD Row Material	STANDARD	UNIT	RESULTS &Tolerances
Determination of Density	TS-EN-ISO 1183-2	g/cm ³	0,898±0.10
Hardness	TS -EN ISO 868	Shore A	85±5
Tensile Strength	TS EN ISO 527-1	Mpa	19,5
Elongation &Break	TS 1398-1 EN ISO 527-1	%	≥10
Determination of ash	TS 336 ISO 247	%	≤10

Visible Defects	-	-	None
Material	-	-	polypropylene copolymer
Colour	-	-	Black
Height	-	mm	26 to 35
Head diameter	-	mm	120
Base diameter	-	mm	200
Centric Load	-	-	-
Visible cumulated threaded height (0 mm)	-	kN	≤ 40
Centric Load	-	-	-
Visible cumulated threaded height (9 mm)	-	kN	≥ 10
Water Absorption (Fully diving method)	-	48 hrs	%0,1
Service Temperature	-	°C	-30 to 70

Prepared by IPM	Controlled by TQM	Confirmed by GM
		

